

Inside furrow variable working



STANDARD EQUIPMENT

Modular chassis

Joints with pins and bushes wear-proof

Skimmer coulter mouldboard

Hydraulic adjustment inside-outside furrow

Fixed beam

Security bolt

Working width for mouldboards of 41 cm or 45 cm

ACCESSORIES

Working depth adjusting wheel (iron, rubber)

Lifting system of the last body with the chassis

Strip mouldboard

Price deduction for skimmer mouldboard if not required – each

	MOD.	Trattori <i>Tractors</i>	largh. lavoro <i>working width</i>	prof. lavoro <i>working depth</i>	peso <i>weight</i>
		HP	mm	mm	Kg
BIVOMERI <i>2 BODIES</i>	ABFS 27	120/140	820 o 900	300/400	950
	ABFS 30	125/150	820 o 900	300/400	1000
	ABFS 40	145/160	820 o 900	350/450	1100
TRIVOMERI <i>3 BODIES</i>	ATFS 27	130/200	1300 o 1350	300/400	1200
	ATFS 30	160/220	1300 o 1350	300/400	1200
	ATFS 40	180/240	1300 o 1350	350/450	1400
QUADRIVOMERI <i>4 BODIES</i>	AQFS 27	180/250	1640 o 1800	300/400	1500
	AQFS 30	190/280	1640 o 1800	300/400	1540
	AQFS 40	260/300	1640 o 1800	350/450	1700